

LIMEA PRO HWD

Hermetic luminaire LIMEA PRO HWD, with a power of 20/26/33/40 W, high light efficacy 155 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP66, providing protection against the ingress of dust and water jets. IK10 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	20/26/33/40 W	Voltage	230 V
Luminous flux*	6200 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
IK	10	Degree of protection (IP)	IP66

Technical data

Power	20/26/33/40 W
Nominal current	175 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	6200 lm (360°)
Luminous flux**	3000-6000 lm (360°)
Lamp efficacy	155 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	10
Degree of protection (IP)	IP66
Colour	Gray/White
Dimension (AxBxC)	1200x80x68 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 22 pcs per line ,

