


opal light line


20W



48V profiles



Code	Finishing	Length mm	Color temperature	Optic	Lm Source	Lm System	Power pack type
6525-63-663	Nero - Black	605	2700K	Diffuser	2236	992	On/Off
6525-63-666	Nero - Black	605	2700K	Diffuser	2236	992	DALI
6525-62-663	Nero - Black	605	3000K	Diffuser	2480	1061	On/Off
6525-62-666	Nero - Black	605	3000K	Diffuser	2480	1061	DALI



Net weight
0,30 Kg

65x65x645
0,40 Kg

CE


IP20 IK04

Energy Class 2700K

Energy Class 3000K

Years Warranty

external corner




48V profiles



Input voltage	Amb. temp.	Power	Driver	CRI
48V DC	-20° +35°C	20W	Included	> 90

Code	Finishing	Angle	Color temperature	Optic	Lm Source	Lm System	Power pack type
6525-43-163	Nero - Black	External	2700K	Diffuser	2236	992	On/Off
6525-43-166	Nero - Black	External	2700K	Diffuser	2236	992	DALI
6525-42-163	Nero - Black	External	3000K	Diffuser	2480	1061	On/Off
6525-42-166	Nero - Black	External	3000K	Diffuser	2480	1061	DALI



Net weight
0,30 Kg

 340x360x60
0,40 Kg

CE   IP20 IK04

 F Energy Class 2700K

 E Energy Class 3000K

 3 Years Warranty